



## Amerex Corporation

### RUGGED

- 6 Year Warranty
- Stored Pressure Design
- Dependable Drawn Steel Cylinders
- Durable High Gloss Polyester Powder Paint
- All Metal Valve Construction

#### Brass Valve - Heavy Duty

Chrome Plated Brass Valve Body

Stainless Steel Handle & Lever

#### Aluminum Valve - Light to Medium Duty

Anodized Aluminum Valve Body

Anodized Aluminum Handle & Lever

- Temperature Range -65°F to 120°F

### USER FRIENDLY

- Easy and Economical to Maintain and Service
- Large Loop Pull Pin
- Bar Coded and Bi-lingual Labels

### OPTION

- USCG Approved with Bracket Listed on UL Label
- Chrome Cylinders (See Chart Below)



Aluminum Valve

B417/T

B500/T

B402/T

B443

B456

A411



Brass Valve

B424

B461

B441

423



Available in Wheeled and Stationary Extinguishers

**ABC or Multi-Purpose** extinguishers utilize a specially fluidized and siliconized mono ammonium phosphate dry chemical. It chemically insulates Class A fires by melting at approximately 350°F and coats surface to which it is applied. It smothers and breaks the chain reaction of Class B fires and will not conduct electricity back to the operator.

### Largest selection of size and extinguisher options available

AGENT TYPE	ABC DRY CHEMICAL									
	NOZZLE	ANODIZED ALUMINUM					CHROME PLATED BRASS			
		HOSE & NOZZLE					HOSE & NOZZLE			
DESIGN	B417/B417T	B500/B500T	B402/B402T	B443	B456	A411	B424	B461	B441	423
MODEL NUMBER	1A-10B-C	2A-10B-C	3A-40B-C	3A-40B-C	4A-80B-C	10A-120B-C	2A-10B-C	3A-40B-C	4A-80-B-C	10A-120B-C
UL & ULC RATING	1A-10B-C	2A-10B-C	3A-40B-C	3A-40B-C	4A-80B-C	10A-120B-C	2A-10B-C	3A-40B-C	4A-80-B-C	10A-120B-C
CAPACITY (LBS.)	2.5	5	5	6	10	20	5	6	10	20
SHIPPING WT. (LBS.)	5.25/5.5	9.25/9.5	9.25/9.5	12.75	18	38	10.5	13.75	19	39
HEIGHT (IN.)	15.5	15.25	15.25	16	20	24	15.5	16.25	20.5	24
WIDTH (IN.)	5.75	7.25	7.25	7.75	7.75	10.25	8	8.5	8.75	10.25
DEPTH (IN.)	3	4.25	4.25	5	5	7	4.25	5	5	7
RANGE (INITIAL- FT)	9-15	12-18	12-18	15-21	15-21	15-21	12-18	15-21	15-21	15-21
DISCHARGE TIME (SEC.)	10	14	14	14.5	20	30	14	14	20	30
FM APPROVED	YES	YES		YES	YES	YES		YES		YES
OPTIONAL CHROME CYLINDER	YES	YES	YES	YES	YES		YES	YES	YES	
INCLUDED BRACKET	WALL/VEHICLE			WALL			WALL			

Manufactured and Tested to ANSI/UL Standards  
Complies with NFPA 10 Standard  
ISO-9001 / ISO-14001 Certified  
**UL LISTED**

**CONFORMS TO TEST STANDARDS:**

CAN/ULC-S504 - ANSI/UL299 &  
CAN/ULC-S508 - ANSI/UL711